

AC/DC Current Probe

CP-05⁺



+ Performance Specifications

Model		CP-05 ⁺			
Test Range		1mA - 400A			
Bandwidth		DC - 200KHz (±3dB)			
Jaw Size		23mm (max)			
Auto Zero at Power-on		√			
Power Supply		9V 6F22 Battery			
Operating Temperature		0°C to 50°C			
Operating Humidity		15% to 70% RH			
DC Current	Range	AC 4A	AC 40A	AC 200A	AC 200A - 400A
	Accuracy	±2.0%rdg ± 5-digit			±3.0%rdg ± 5-digit
	Sensitivity	1mV/10mA	1mV/0.1A	1mV/1A	
AC Current	Range	DC 4A	DC 40A	DC 200A	DC 200 - 400A
	Accuracy	±1.5%rdg ± 5-digit			±3.0%rdg ± 5-digit
	Sensitivity	1mV/10mA	1mV/0.1A	1mV/1A	
Dimension (W x H x D)		180 x 30 x 44mm			
Device Weight		200g			

Specifications subject to change without prior notice.

+ Accessories

The accessories subject to final delivery.



Soft Bag

Продажа измерительных приборов и инструмента:
ТОО «МЕСС-ЭЛЕКТРОНИК»
Адрес: 050009, Республика Казахстан, Алмалинский район,
г. Алматы, улица Толе би, сооружение 202а
Тел. +7 701 126 0577
E-mail: info@mess-electronic.kz
<https://mess-electronic.kz/>